




Tornado PRO


Tornado PRO Twin 1500mm High Output 1 Code: ATORPLED2X5/HO/1/MWS/DM3

Category	Battens and Weatherproofs	
Application	ion Ancillary, Commercial, Education, Healthcare,	
	Hospitality, Industrial, Retail	
Specification	Performance	









- Ultra slim IP65 LED robust non-corrosive batten ideal for industrial applications and ancillary
 areas
- · Unique base design caters for multiple installation methods
- Quick release LED array / gear tray assembly provides the installer the means to faster
 installation / maintenance
- Self-test emergency option with Li-ion battery technology, reducing charge time and running costs

•	High efficiency up	to	161	Lm/W
	ingri onioiono, up	10		L

- Installer friendly embedded features aid accurate and fast installation for any application
- Fast latching / permanently located stainless steel side clips ensure a quick and secure connection
- High output 5ft options available

GENERAL INFORMATION			
Wattage	79W		
Lumens Delivered	13000lm		
Lm/W	161lm/W		
Beam Angle	100/120		
CRI	80		
CCT	4000K		
Input	220-240V		
Operating Temp	0°C - 40°C		
SDCM	3		
UGR	26		

TECHNICAL INFORMATION				
LED				
Grey				
IP65				
1				
Internal / External				
Ceiling, Suspended				
L80 54,000h				
7				
Yes				
70 mm				