



# Tornado PRO

Tornado PRO Twin 1500mm High Output 2  
Code: ATORPLED2X5/HO/2/CF

|               |   |
|---------------|---|
| Category      | Battens and Weatherproofs   |
| Application   | Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Retail |
| Specification | Performance   |



## PRODUCT FEATURES

- Ultra slim IP65 LED robust non-corrosive batten ideal for industrial applications and ancillary areas
- Unique base design caters for multiple installation methods
- Quick release LED array / gear tray assembly provides the installer the means to faster installation / maintenance
- Self-test emergency option with Li-ion battery technology, reducing charge time and running costs
- High efficiency up to 161 Lm/W
- Installer friendly embedded features aid accurate and fast installation for any application
- Fast latching / permanently located stainless steel side clips ensure a quick and secure connection
- High output 5ft options available

| GENERAL INFORMATION |              |
|---------------------|--------------|
| Wattage             | 115W         |
| Lumens Delivered    | 18000lm      |
| Lm/W                | 158lm/W      |
| Beam Angle          | 100/120      |
| CRI                 | 80           |
| CCT                 | 4000K        |
| Input               | 220-240V     |
| Operating Temp      | -10°C - 40°C |
| SDCM                | 3            |
| UGR                 | 28           |

| TECHNICAL INFORMATION          |   |
|--------------------------------|---|
| Light Source                   | LED   |
| Colour / Finish                | Grey  |
| IP Rating                      | IP65  |
| Class Protection               | 1   |
| Internal / External            | Internal / External                           |
| Surface / Recessed / Suspended | Ceiling, Suspended                            |
| Lumen Depreciation             | L80 54,000h                                   |
| Warranty (Years)               | 7   |
| CE Mark                        | Yes   |
| Height                         | 70 mm   |
| Accessories                    | ATORPLED/SSKIT/SINGLE,<br>ATORPLED/SSKIT/TWIN |

