




Tornado PRO


Tornado PRO Twin 1500mm High Output 2 Switch Code: ATORPLED2X5/HO/2/DD1/DM3

Category	Battens and Weatherproofs
Application	Ancillary, Commercial, Education, Healthcare,
	Hospitality, Industrial, Retail
Specification	Performance









- Ultra slim IP65 LED robust non-corrosive batten ideal for industrial applications and ancillary
 areas
- · Unique base design caters for multiple installation methods
- Quick release LED array / gear tray assembly provides the installer the means to faster
 installation / maintenance
- Self-test emergency option with Li-ion battery technology, reducing charge time and running costs

 High efficiency up to 161 Lm/W
--

- Installer friendly embedded features aid accurate and fast installation for any application
- Fast latching / permanently located stainless steel side clips ensure a quick and secure connection
- · High output 5ft options available

GENERAL INFORMATION		
Wattage	115W	
Lumens Delivered	18000lm	
Lm/W	158lm/W	
Beam Angle	100/120	
CRI	80	
CCT	4000K	
Input	220-240V	
Operating Temp	0°C - 40°C	
SDCM	3	
UGR	28	

TECHNICAL INFORMATION			
LED			
Grey			
IP65			
1			
Internal / External			
Ceiling, Suspended			
L80 54,000h			
7			
Yes			
70 mm			

