




Tornado PRO


Tornado PRO Twin 1500mm High Output 2 Code: ATORPLED2X5/HO/2/MWS

Category	Battens and Weatherproofs		
Application	Ancillary, Commercial, Education, Healthcare,		
	Hospitality, Industrial, Retail		
Specification	Performance		









- Ultra slim IP65 LED robust non-corrosive batten ideal for industrial applications and ancillary
 areas
- · Unique base design caters for multiple installation methods
- Quick release LED array / gear tray assembly provides the installer the means to faster
 installation / maintenance
- Self-test emergency option with Li-ion battery technology, reducing charge time and running costs

•	High	efficiency	up to	161	Lm/W
---	------	------------	-------	-----	------

- Installer friendly embedded features aid accurate and fast installation for any application
- Fast latching / permanently located stainless steel side clips ensure a quick and secure connection
- High output 5ft options available

GENER	RAL INFORMATION	
Wattage	130W	
Lumens Delivered	18000lm	
Lm/W	158lm/W	
Beam Angle	100/120	
CRI	80	
ССТ	4000K	
Input	220-240V	
Operating Temp	-10°C - 40°C	
SDCM	3	
UGR	28	
Product Weight without Packaging	1.965 kg	

TECHNICAL INFORMATION				
Light Source	LED	_		
Colour / Finish	Grey			
IP Rating	IP65			
Class Protection	1			
Internal / External	Internal / External			
Surface / Recessed / Suspended	Ceiling, Suspended			
Lumen Depreciation	L80 54,000h	_		
Warranty (Years)	7			
CE Mark	Yes			
Height	70 mm			
Accessories	ATORPLED/SSKIT/SINGLE,			
	ATORPLED/SSKIT/TWIN			