





@ansell_lighting









Tornado PRO

Tornado PRO Twin 1500mm Code: ATORPLED2X5

| Category | Battens and Weatherproofs | |
|---------------|---|--|
| Application | Ancillary, Commercial, Education, Healthcare, | |
| | Hospitality, Industrial, Retail | |
| Specification | Performance | |







- Ultra slim IP65 LED robust non-corrosive batten ideal for industrial applications and ancillary areas
- · Unique base design caters for multiple installation methods
- Quick release LED array / gear tray assembly provides the installer the means to faster installation / maintenance
- Self-test emergency option with Li-ion battery technology, reducing charge time and running costs
- High efficiency up to 161 Lm/W
- Installer friendly embedded features aid accurate and fast installation for any application
- Fast latching / permanently located stainless steel side clips ensure a quick and secure connection
- High output 5ft options available

| GENERAL INFORMATION | | | |
|----------------------------------|--------------|--|--|
| Wattage | 60W | | |
| Lumens Delivered | 6300lm | | |
| Lm/W | 103lm/W | | |
| Beam Angle | 100/120 | | |
| CRI | 80 | | |
| CCT | 4000K | | |
| Input | 220-240V | | |
| Operating Temp | -10°C - 40°C | | |
| SDCM | 3 | | |
| Product Weight without Packaging | 2.226 kg | | |
| | | | |

| TECHNICAL INFORMATION | | | |
|--------------------------------|------------------------|--|--|
| Light Source | LED | | |
| Colour / Finish | Grey | | |
| IP Rating | IP65 | | |
| Class Protection | 1 | | |
| Internal / External | Internal / External | | |
| Surface / Recessed / Suspended | Ceiling, Suspended | | |
| Lumen Depreciation | L80 54,000h | | |
| Warranty (Years) | 7 | | |
| CE Mark | Yes | | |
| Height | 70 mm | | |
| Accessories | ATORPLED/SSKIT/SINGLE, | | |
| | ATORPLED/SSKIT/TWIN | | |

www.ansell-lighting.com Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750

