





Tornado PRO

Tornado PRO Twin 1800mm Switch Dim Self-Test Code: ATORPLED2X6/DD1/M3

Category	Battens and Weatherproofs
Application	Ancillary, Commercial, Education, Healthcare,
	Hospitality, Industrial, Retail
Specification	Performance







- Ultra slim IP65 LED robust non-corrosive batten ideal for industrial applications and ancillary
 areas
- · Unique base design caters for multiple installation methods
- Quick release LED array / gear tray assembly provides the installer the means to faster
 installation / maintenance
- Self-test emergency option with Li-ion battery technology, reducing charge time and running costs

 High efficiency up to 161 Lm/W
--

- Installer friendly embedded features aid accurate and fast installation for any application
- Fast latching / permanently located stainless steel side clips ensure a quick and secure connection
- High output 5ft options available

GENER	RAL INFORMATION
Wattage	78W
Lumens Delivered	8200lm
Lm/W	105lm/W
Beam Angle	100/120
CRI	80
ССТ	4000K
Input	220-240V
Operating Temp	0°C - 40°C
SDCM	3
Product Weight without Packaging	2.46 kg

TECHNI	CAL INFORMATION	
Light Source	LED	
Colour / Finish	Grey	
IP Rating	IP65	
Class Protection	1	
Internal / External	Internal / External	
Surface / Recessed / Suspended	Ceiling, Suspended	
Lumen Depreciation	L80 54,000h	
Warranty (Years)	7	
CE Mark	Yes	
Height	70 mm	
Accessories	ATORPLED/SSKIT/SINGLE,	
	ATORPLED/SSKIT/TWIN	