




Tornado PRO


Tornado PRO Twin 1800mm Switch Dim Code: ATORPLED2X6/DD1/MWS

Category	Battens and Weatherproofs		
Application	Ancillary, Commercial, Education, Healthcare,		
	Hospitality, Industrial, Retail		
Specification	Performance		









- Ultra slim IP65 LED robust non-corrosive batten ideal for industrial applications and ancillary areas
- · Unique base design caters for multiple installation methods
- Quick release LED array / gear tray assembly provides the installer the means to faster
 installation / maintenance
- Self-test emergency option with Li-ion battery technology, reducing charge time and running costs

•	Hiah	efficiency	up t	0 161	Lm/W
	ingn	cincicity	upr	0 101	

- Installer friendly embedded features aid accurate and fast installation for any application
- Fast latching / permanently located stainless steel side clips ensure a quick and secure connection
- High output 5ft options available

	GENERAL INFORMATION
Wattage	78W
Lumens Delivered	8200lm
Lm/W	105lm/W
Beam Angle	100/120
CRI	80
CCT	4000K
Input	220-240V
Operating Temp	-10°C - 40°C
SDCM	3
Product Weight without Packagi	ng 2.536 kg

TECHNICAL INFORMATION					
Light Source	LED				
Colour / Finish	Grey				
IP Rating	IP65				
Class Protection	1				
Internal / External	Internal / External				
Surface / Recessed / Suspended	Ceiling, Suspended				
Lumen Depreciation	L80 54,000h				
Warranty (Years)	7				
CE Mark	Yes				
Height	70 mm				
Accessories	ATORPLED/SSKIT/SINGLE,				
	ATORPLED/SSKIT/TWIN				