













Tornado PRO

Tornado PRO Twin 1800mm Microwave Sensor Code: ATORPLED2X6/MWS

Category	Battens and Weatherproofs
Application	Ancillary, Commercial, Education, Healthcare,
	Hospitality, Industrial, Retail
Specification	Performance







- Ultra slim IP65 LED robust non-corrosive batten ideal for industrial applications and ancillary High efficiency up to 161 Lm/W areas
- · Unique base design caters for multiple installation methods
- Quick release LED array / gear tray assembly provides the installer the means to faster installation / maintenance
- Self-test emergency option with Li-ion battery technology, reducing charge time and running costs
- Installer friendly embedded features aid accurate and fast installation for any application
- Fast latching / permanently located stainless steel side clips ensure a quick and secure connection
- High output 5ft options available

GENER	RAL INFORMATION	
Wattage	72W	
Lumens Delivered	8200lm	
Lm/W	105lm/W	
Beam Angle	100/120	
CRI	80	
CCT	4000K	
Input	220-240V	
Operating Temp	-10°C - 40°C	
SDCM	3	
Product Weight without Packaging	2.417 kg	

TECHNICAL INFORMATION			
Light Source	LED		
Colour / Finish	Grey		
IP Rating	IP65		
Class Protection	1		
Internal / External	Internal / External		
Surface / Recessed / Suspended	Ceiling, Suspended		
Lumen Depreciation	L80 54,000h		
Warranty (Years)	7		
CE Mark	Yes		
Height	70 mm		
Accessories	ATORPLED/SSKIT/SINGLE,		
	ATORPLED/SSKIT/TWIN		

www.ansell-lighting.com Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750

