













Tornado PRO

Tornado PRO 1200mm Corridor Function Code: ATORPLED4/CF









- Ultra slim IP65 LED robust non-corrosive batten ideal for industrial applications and ancillary areas
- Unique base design caters for multiple installation methods
- Quick release LED array / gear tray assembly provides the installer the means to faster installation / maintenance
- Self-test emergency option with Li-ion battery technology, reducing charge time and running costs
- High efficiency up to 161 Lm/W
- $\bullet \ \ \text{Installer friendly embedded features aid accurate and fast installation for any application}$
- Fast latching / permanently located stainless steel side clips ensure a quick and secure connection
- High output 5ft options available

GENERAL INFORMATION		
Wattage	20W	
Lumens Delivered	2300lm	
Lm/W	117lm/W	
Beam Angle	100/120	
CRI	80	
ССТ	4000K	
Input	220-240V	
Operating Temp	-10°C - 40°C	
SDCM	3	
Product Weight without Packaging	1.734 kg	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	Grey	
IP Rating	IP65	
Class Protection	1	
Internal / External	Internal / External	
Surface / Recessed / Suspended	Ceiling, Suspended	
Lumen Depreciation	L80 54,000h	
Warranty (Years)	7	
CE Mark	Yes	
Height	70 mm	

www.ansell-lighting.com Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750

