





Tornado PRO

Tornado PRO 1800mm DSI Self-Test Emergency Code: ATORPLED6/DD2/M3

| Category | Battens and Weatherproofs |
|---------------|---|
| Application | Ancillary, Commercial, Education, Healthcare, |
| | Hospitality, Industrial, Retail |
| Specification | Performance |







- Ultra slim IP65 LED robust non-corrosive batten ideal for industrial applications and ancillary
 areas
- · Unique base design caters for multiple installation methods
- Quick release LED array / gear tray assembly provides the installer the means to faster
 installation / maintenance
- Self-test emergency option with Li-ion battery technology, reducing charge time and running costs

| High efficiency up to 161 Lm/W |
|--|
|--|

- Installer friendly embedded features aid accurate and fast installation for any application
- Fast latching / permanently located stainless steel side clips ensure a quick and secure connection
- High output 5ft options available

| GENERAL INFORMATION | | | |
|----------------------------------|------------|--|--|
| Wattage | 35W | | |
| Lumens Delivered | 3700lm | | |
| Lm/W | 106lm/W | | |
| Beam Angle | 100/120 | | |
| CRI | 80 | | |
| CCT | 4000K | | |
| Input | 220-240V | | |
| Operating Temp | 0°C - 40°C | | |
| SDCM | 3 | | |
| Product Weight without Packaging | 0.01 kg | | |

| TECHNICAL INFORMATION | | | | |
|--------------------------------|------------------------|--|--|--|
| Light Source | LED | | | |
| Colour / Finish | Grey | | | |
| IP Rating | IP65 | | | |
| Class Protection | 1 | | | |
| Internal / External | Internal / External | | | |
| Surface / Recessed / Suspended | Ceiling, Suspended | | | |
| Lumen Depreciation | L80 54,000h | | | |
| Warranty (Years) | 7 | | | |
| CE Mark | Yes | | | |
| Height | 70 mm | | | |
| Accessories | ATORPLED/SSKIT/SINGLE, | | | |
| | ATORPLED/SSKIT/TWIN | | | |