


Tornado PRO


Tornado PRO 1800mm DALI DALI-Emergency Code: ATORPLED6/DD3/DM3

Category	Battens and Weatherproofs		
Application Ancillary, Commercial, Education, Healthcar			
	Hospitality, Industrial, Retail		
Specification	Performance		









- Ultra slim IP65 LED robust non-corrosive batten ideal for industrial applications and ancillary
 areas
- · Unique base design caters for multiple installation methods
- Quick release LED array / gear tray assembly provides the installer the means to faster
 installation / maintenance
- Self-test emergency option with Li-ion battery technology, reducing charge time and running costs

•	Hiah	efficiency	up t	0 161	Lm/W
	ingn	cincicity	upr	0 101	

- Installer friendly embedded features aid accurate and fast installation for any application
- Fast latching / permanently located stainless steel side clips ensure a quick and secure connection
- High output 5ft options available

GENER	AL INFORMATION
Wattage	35W
Lumens Delivered	3700lm
Lm/W	106lm/W
Beam Angle	100/120
CRI	80
ССТ	4000K
Input	220-240V
Operating Temp	0°C - 40°C
SDCM	3
Product Weight without Packaging	0.01 kg

TECHNICAL INFORMATION				
Light Source	LED			
Colour / Finish	Grey			
IP Rating	IP65			
Class Protection	1			
Internal / External	Internal / External			
Surface / Recessed / Suspended	Ceiling, Suspended			
Lumen Depreciation	L80 54,000h			
Warranty (Years)	7			
CE Mark	Yes			
Height	70 mm			
Accessories	ATORPLED/SSKIT/SINGLE,			
	ATORPLED/SSKIT/TWIN			

