



# Tornado PRO

Tornado PRO 1800mm DALI-Emergency  
Code: ATORPLED6/DM3

|                      |   |
|----------------------|---|
| <b>Category</b>      | Battens and Weatherproofs   |
| <b>Application</b>   | Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Retail |
| <b>Specification</b> | Performance   |



## PRODUCT FEATURES

- Ultra slim IP65 LED robust non-corrosive batten ideal for industrial applications and ancillary areas
- Unique base design caters for multiple installation methods
- Quick release LED array / gear tray assembly provides the installer the means to faster installation / maintenance
- Self-test emergency option with Li-ion battery technology, reducing charge time and running costs
- High efficiency up to 161 Lm/W
- Installer friendly embedded features aid accurate and fast installation for any application
- Fast latching / permanently located stainless steel side clips ensure a quick and secure connection
- High output 5ft options available

| GENERAL INFORMATION              |            |
|----------------------------------|------------|
| Wattage                          | 35W        |
| Lumens Delivered                 | 3700lm     |
| Lm/W                             | 106lm/W    |
| Beam Angle                       | 100/120    |
| CRI                              | 80         |
| CCT                              | 4000K      |
| Input                            | 220-240V   |
| Operating Temp                   | 0°C - 40°C |
| SDCM                             | 6          |
| Product Weight without Packaging | 0.085 kg   |

| TECHNICAL INFORMATION          |   |
|--------------------------------|---|
| Light Source                   | LED   |
| Colour / Finish                | Grey  |
| IP Rating                      | IP65  |
| Class Protection               | 1   |
| Internal / External            | Internal / External                           |
| Surface / Recessed / Suspended | Ceiling, Suspended                            |
| Lumen Depreciation             | L80 54,000h                                   |
| Warranty (Years)               | 7   |
| CE Mark                        | Yes   |
| Height                         | 70 mm   |
| Accessories                    | ATORPLED/SSKIT/SINGLE,<br>ATORPLED/SSKIT/TWIN |

