





@ansell_lighting





in Ansell Lighting




Tornado PRO


Tornado PRO 1800mm Microwave Sensor DALI-Code: ATORPLED6/MWS/DM3

Category	Battens and Weatherproofs
Application	Ancillary, Commercial, Education, Healthcare,
	Hospitality, Industrial, Retail
Specification	Performance









- Ultra slim IP65 LED robust non-corrosive batten ideal for industrial applications and ancillary areas
- · Unique base design caters for multiple installation methods
- Quick release LED array / gear tray assembly provides the installer the means to faster installation / maintenance
- Self-test emergency option with Li-ion battery technology, reducing charge time and running costs
- High efficiency up to 161 Lm/W
- Installer friendly embedded features aid accurate and fast installation for any application
- Fast latching / permanently located stainless steel side clips ensure a quick and secure connection
- High output 5ft options available

GENERAL INFORMATION			
Wattage	35W		
Lumens Delivered	3700lm		
Lm/W	106lm/W		
Beam Angle	100/120		
CRI	80		
CCT	4000K		
Input	220-240V		
Operating Temp	0°C - 40°C		
SDCM	3		
Product Weight without Packaging	0.01 kg		

TECHNICAL INFORMATION			
Light Source	LED		
Colour / Finish	Grey		
IP Rating	IP65		
Class Protection	1		
Internal / External	Internal / External		
Surface / Recessed / Suspended	Ceiling, Suspended		
Lumen Depreciation	L80 54,000h		
Warranty (Years)	7		
CE Mark	Yes		
Height	70 mm		
Accessories	ATORPLED/SSKIT/SINGLE,		
	ATORPLED/SSKIT/TWIN		