Trinity

Part of the Commercial Linear product category

Model	Trinity CCT UGR19 Surface Linear 1500mm
Code	ATRI5/1
Application	Commercial, Education, Healthcare

GENERAL INFORMATION

Input	220-240V
Wattage	23W - 40W
Operating Temp	-20°C to 40°C
Lumens Delivered	2900lm - 5000lm (4000K)
lm/W	130lm/W
CCT	3000K/4000K/6000K
UGR	18
Beam Angle	90

MATERIAL INFORMATION

Main Material	Steel
Diffuser Material	PMMA
Colour / Finish	White

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	3
CRI	80
Internal / External	Internal
Surface / Recessed / Suspended	Ceiling
Power Factor	0.95
L70 @ 25°C	L70 B50 100,000h

PRODUCT FEATURES

- High specification UGR<19 surface linear suitable for healthcare, education and commercial applications
- UGR<19 (unified glare rating) compliant luminaire greatly reduces glare for visual comfort
- Retractable and lockable end caps ensure suitability for education applications
- Power and CCT selectable between 3000K, 4000K and 6000K; offering a choice of 2 outputs and 3 colour temperature options, in one luminaire
- Steel body with polycarbonate diffuser and end caps

ACCESSORIES

ASK1	Suspension Kit





Trinity

Part of the Commercial Linear product category

Model	Trinity CCT UGR19 Surface Linear 1500mm
Code	ATRI5/1
Application	Commercial, Education, Healthcare











