Tridon

Part of the Wall Lights product category

Model	Tridon CCT Grey
Code	ATRILED/G
Application	Ancillary, Hospitality, Industrial, Outdoor, Residential, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	8W
Operating Temp	-20°C - 40°C
Lumens Delivered	700lm (4000K)
lm/W	88lm/W (4000K)
CCT	3000/4000K
Beam Angle	120

MATERIAL INFORMATION

Diffuser Material	Polycarbonate
Product Weight without Packaging	1.583 kg
Colour / Finish	Graphite
Height	320 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	5
CRI	80
Internal / External	External
Surface / Recessed / Suspended	Wall
Power Factor	0.6
L70 @ 25°C	L70 B50 60,000h

PRODUCT FEATURES

- IP66 rated die-cast aluminium wall light with opal polycarbonate diffuser suitable for commercial, hospitality and industrial applications
- Internal CCT selector switch allows the installer to choose the CCT between 3000K and 4000K at the point of installation
- Rear fixing points allowing the option for BESA box mounting
- Horizontal side pilot holes accepting 20mm surface conduit entries
- Tamper-proof stainless steel allen key screws





Tridon

Part of the Wall Lights product category

Model	Tridon CCT Grey
Code	ATRILED/G
Application	Ancillary, Hospitality, Industrial, Outdoor, Residential, Retail



