



Category	Feature Lighting	
Application	Commercial, Education, Healthcare, Hospitality,	
	Outdoor, Residential, Retail	
Specification	Architectural	

Turlock

Turlock 175 LED Walkover IP67 Code: ATURWOLED/175







- High performance inground uplight suitable for commercial, hospitality and residential applications
- Die-cast aluminium construction with 316L stainless steel top frame
- Static load test to 2000kg; suitable for vehicular and pedestrian traffic
- · Powered by HEP

- Supplied c/w installation housing for additional protection and ease of installation
- Pre-wired with 1 metre of rubber insulated cable
- Triac dimmable as standard

Wattage 8 Lumens Delivered 870Im Lm/W 110Im/W Beam Angle 20 CRI 90 CCT 4000K Input 220-240V Operating Temp -20°C - 25°C SDCM 3	
Lm/W 110lm/W Beam Angle 20 CRI 90 CCT 4000K Input 220-240V Operating Temp -20°C - 25°C	
Beam Angle 20 CRI 90 CCT 4000K Input 220-240V Operating Temp -20°C - 25°C	
CRI 90 CCT 4000 K Input 220-240 V Operating Temp -20°C - 25°C	
CCT 4000K Input 220-240V Operating Temp -20°C - 25°C	
Input 220-240V Operating Temp -20°C - 25°C	
Operating Temp -20°C - 25°C	
· · ·	
CDOM 2	
SDOM 3	
Cut-Out Size 155mm	
Product Weight without Packaging 2.126 kg	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	Stainless Steel	
IP Rating	IP67	
IK Rating	IK10	
Class Protection	1	
Internal / External	External	
Surface / Recessed / Suspended	Recessed	
Warranty (Years)	5	
CE Mark	Yes	
Diameter	175 mm	











Category	Feature Lighting
Application	Commercial, Education, Healthcare, Hospitality,
	Outdoor, Residential, Retail
Specification	Architectural

Turlock

Turlock 175 LED Walkover IP67 Code: ATURWOLED/175







