



Twin Spot

Part of the Emergency product category



Model	Twin Spot
Code	ATWS/1/NM
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	3.5W
Operating Temp	0°C - 40°C
Lumens Delivered	440lm
lm/W	125lm/W
CCT	6500K

MATERIAL INFORMATION

Main Material	Iron
Product Weight without	1.85 kg
Packaging	
Colour / Finish	White
Height	107 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	6
CRI	70
Internal / External	Internal
Surface / Recessed / Suspended	Wall
Power Factor	0.35
L70 @ 25°C	L70 B50 60,000h

PRODUCT FEATURES

- Twin LED emergency floodlighting for industrial applications
- LiFePO4 Lithium battery provides enhanced product lifetime
- Robust metal enclosure in an opal colour
- Moulded polycarbonate heads
- Selectable self-test/manual test as standard.

ACCESSORIES

ASBP/7/LI	3.2V 5500mAh LiFePO4 Battery - ATWS/1
-----------	---------------------------------------





Twin Spot



Part of the Emergency product category

Model	Twin Spot
Code	ATWS/1/NM
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Retail

