



Unity Downlight

Part of the Downlights product category



Model	Unity Multi Pivot Single 4000K Downlight
Code	AULED1/SMP
Application	Ancillary, Commercial, Education, Hospitality, Residential, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	15
Operating Temp	-20°C - 25°C
Lumens Delivered	1000lm
lm/W	73lm/W
CCT	4000K
UGR	14
Beam Angle	50

MATERIAL INFORMATION

Main Material	Aluminium
Product Weight without	0.609 kg
Packaging	
Colour / Finish	White
Height	106 mm

TECHNICAL INFORMATION

Class Protection	2
Light Source	LED
SDCM (Initial Macadam)	3
CRI	90
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Power Factor	0.55
L70 @ 25°C	L70 B50 60,000h

PRODUCT FEATURES

- Square and Rectangular recessed adjustable architectural downlight suitable for commercial, hospitality and retail applications
- Full 360° head rotation and 90° tilting capability
- Retractable head design allows for a range of installation applications
- Black trim provides excellent glare control
- Steel housing with die-cast aluminium body for excellent thermal management





Unity Downlight



Part of the Downlights product category

- Model** Unity Multi Pivot Single 4000K Downlight
Code AULED1/SMP
Application Ancillary, Commercial, Education, Hospitality, Residential, Retail

