# Unity Downlight

Part of the Downlights product category

| | |
|---|---|
| **Model** | Unity Multi Pivot Single 4000K Downlight |
| **Code** | AULED1/SMP |
| **Application** | Ancillary, Commercial, Education, Hospitality, Residential, Retail |



## GENERAL INFORMATION

| | |
|---|---|
| **Input** | 220-240V |
| **Wattage** | 15 |
| **Operating Temp** | -20°C - 25°C |
| **Lumens Delivered** | 1000lm |
| **lm/W** | 73lm/W |
| **CCT** | 4000K |
| **UGR** | 14 |
| **Beam Angle** | 50 |

## MATERIAL INFORMATION

| | |
|---|---|
| **Main Material** | Aluminium |
| **Product Weight without Packaging** | 0.609 kg |
| **Colour / Finish** | White |
| **Height** | 106 mm |

## TECHNICAL INFORMATION

| | |
|---|---|
| **Class Protection** | 2 |
| **Light Source** | LED |
| **SDCM (Initial Macadam)** | 3 |
| **CRI** | 90 |
| **Internal / External** | Internal |
| **Surface / Recessed / Suspended** | Recessed |
| **Power Factor** | 0.55 |
| **L70 @ 25°C** | L70 B50 60,000h |

## PRODUCT FEATURES

- Square and Rectangular recessed adjustable architectural downlight suitable for commercial, hospitality and retail applications
- Full 360° head rotation and 90° tilting capability
- Retractable head design allows for a range of installation applications
- Black trim provides excellent glare control
- Steel housing with die-cast aluminium body for excellent thermal management

# Unity Downlight

Part of the Downlights product category

| | |
|---|---|
| **Model** | Unity Multi Pivot Single 4000K Downlight |
| **Code** | AULED1/SMP |
| **Application** | Ancillary, Commercial, Education, Hospitality, Residential, Retail |




