



Category	Downlights
Application	Ancillary, Commercial, Education, Hospitality, Residential, Retail
Specification	Architectural

# Unity S and R

32W Unity S 4000K LED Downlight

Code: AULED1/SQU

## PRODUCT FEATURES

- Square and Rectangular recessed adjustable architectural downlight suitable for commercial, hospitality and retail applications
- Black trim provides excellent glare control
- Remote driver with plug and play connection
- Powered by Tridonic
- Fully adjustable tilt angle 30° on two axis
- Steel housing with die-cast aluminium body for good thermal management
- Dimmable options


## GENERAL INFORMATION

Wattage	36W
Lumens Delivered	3100lm
Lm/W	88lm/W
Beam Angle	40
CRI	90
CCT	4000K
Input	220-240V
Operating Temp	-20°C - 25°C
SDCM	3
UGR	10
Cut-Out Size	160x160
Energy efficiency class	E
Product Weight without Packaging	1.376 kg

## TECHNICAL INFORMATION

Light Source	LED
Colour / Finish	White
IP Rating	IP20
IK Rating	IK02
Class Protection	2
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Warranty (Years)	5
CE Mark	Yes
Height	152 mm





<b>Category</b>	Downlights
<b>Application</b>	Ancillary, Commercial, Education, Hospitality, Residential, Retail
<b>Specification</b>	Architectural

# Unity S and R

32W Unity S 4000K LED Downlight

**Code:** AULED1/SQU

