













Unity 100

Unity 100 Wallwash Cool White DSI Code: AULED100WW/DD2











PRODUCT FEATURES

- Recessed adjustable architectural wallwash with 355° rotation suitable for commercial, hospitality and retail applications
- 30° cut-off angle in the horizontal position
- Remote driver with plug and play connection
- · Powered by Tridonic

- Adjustable tilt angle from -15° to 45°
- Die-cast aluminium body and heatsink for good thermal management
- · Dimmable options

| GENERAL INFORMATION | | |
|--------------------------------|--------------|--|
| Wattage | 15W | |
| Lumens Delivered | 1300lm | |
| Lm/W | 84lm/W | |
| Beam Angle | 55 | |
| CRI | 90 | |
| CCT | 4000K | |
| Input | 220-240V | |
| Operating Temp | -20°C - 25°C | |
| SDCM | 3 | |
| UGR | 17 | |
| Cut-Out Size | 100mm | |
| Product Weight without Packagi | ng 1.007 kg | |

| TECHNICAL INFORMATION | | |
|--------------------------------|-------------|--|
| Light Source | LED | |
| Colour / Finish | White | |
| IP Rating | IP20 | |
| Class Protection | 2 | |
| Internal / External | Internal | |
| Surface / Recessed / Suspended | Recessed | |
| Lumen Depreciation | L70 60,000h | |
| Warranty (Years) | 5 | |
| CE Mark | Yes | |
| Diameter | 112 mm | |
| Height | 88 mm | |