







# Unity 125

Unity 125 Downlight Cool White DALI-Emergency  
Code: AULED125D/DM3

|               |  |
|---------------|--|
| Category      | Downlights   |
| Application   | Ancillary, Commercial, Education, Hospitality, Residential, Retail |
| Specification | Architectural  |



- IP44 compact high performance architectural downlight suitable for commercial, hospitality and retail applications
- Mirror finished anodized reflector
- Remote driver with plug and play connection
- Powered by Tridonic
- Die-cast aluminium construction, powder coated and 30° cut-off angle
- Anti-glare design to create visual comfort
- Dimmable and emergency options

| GENERAL INFORMATION              |            |
|----------------------------------|------------|
| Wattage                          | 21W        |
| Lumens Delivered                 | 1500lm     |
| Lm/W                             | 72lm/W     |
| Beam Angle                       | 65         |
| CRI                              | 90         |
| CCT                              | 4000K      |
| Input                            | 220-240V   |
| Operating Temp                   | 0°C - 25°C |
| SDCM                             | 3          |
| UGR                              | 17         |
| Cut-Out Size                     | 125mm      |
| Product Weight without Packaging | 1.112 kg   |

| TECHNICAL INFORMATION          |             |
|--------------------------------|-------------|
| Light Source                   | LED         |
| Colour / Finish                | White       |
| IP Rating                      | IP44        |
| Class Protection               | 2           |
| Internal / External            | Internal    |
| Surface / Recessed / Suspended | Recessed    |
| Lumen Depreciation             | L80 60,000h |
| Warranty (Years)               | 5           |
| CE Mark                        | Yes         |
| Diameter                       | 138 mm      |
| Height                         | 105 mm      |

