





Downlights

Residential, Retail









Unity 125

Unity 125 Downlight Cool White OCTO Smart Code: AULED125D/OCTO








Category

Application

Specification



Ancillary, Commercial, Education, Hospitality,

PRODUCT FEATURES

- IP44 compact high performance architectural downlight suitable for commercial, hospitality and retail applications
- Mirror finished anodized reflector
- Remote driver with plug and play connection
- · Powered by Tridonic

- Die-cast aluminium construction, powder coated and 30° cut-off angle
- · Anti-glare design to create visual comfort
- Dimmable and emergency options

	GENERAL INFORMATION
Wattage	21W
Lumens Delivered	1500lm
Lm/W	72lm/W
Beam Angle	65
CRI	90
CCT	4000K
Input	220-240V
Operating Temp	-20°C - 25°C
SDCM	3
UGR	17
Cut-Out Size	125mm
Product Weight without Packag	ng 0.76 kg

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	White	
IP Rating	IP44	
Class Protection	2	
Internal / External	Internal	
Surface / Recessed / Suspended	Recessed	
Lumen Depreciation	L80 60,000h	
Warranty (Years)	5	
CE Mark	Yes	
Diameter	138 mm	
Height	105 mm	

Belfast: +44 (0) 2890 773750