

Unity 125

Unity 125 Downlight Warm White Switch Dim Self-Code: AULED125D/WW/DD1/SM3



Category	Downlights	
Application	Ancillary, Commercial, Education, Hospitality,	
	Residential, Retail	
Specification	Architectural	



PRODUCT FEATURES

- IP44 compact high performance architectural downlight suitable for commercial, hospitality
 and retail applications
- Mirror finished anodized reflector
- Remote driver with plug and play connection
- Powered by Tridonic

GENERAL INFORMATION					
Wattage	21W				
Lumens Delivered	1400lm				
Lm/W	66Im/W				
Beam Angle	65				
CRI	90				
CCT	4000K				
Input	220-240V				
Operating Temp	0°C - 25°C				
SDCM	3				
UGR	17				
Cut-Out Size	125mm				

TECHNICAL INFORMATION					
Light Source	LED				
Colour / Finish	White				
IP Rating	IP44				
Class Protection	2				
Internal / External	Internal				
Surface / Recessed / Suspended	Recessed				
Lumen Depreciation	L80 60,000h				
Warranty (Years)	5				
CE Mark	Yes				
Diameter	138 mm				
Height	105 mm				

Die-cast aluminium construction, powder coated and 30° cut-off angle
 Anti-glare design to create visual comfort

Dimmable and emergency options