




Unity 125

Unity 125 Downlight Warm White 1-10V Self-Test Code: AULED125D/WW/DD4/SM3

| Category | Downlights |
|---------------|--|
| Application | Ancillary, Commercial, Education, Hospitality, |
| | Residential, Retail |
| Specification | Architectural |
| | |



PRODUCT FEATURES

- IP44 compact high performance architectural downlight suitable for commercial, hospitality
 Die-cast aluminium construction, powder coated and 30° cut-off angle and retail applications
- Mirror finished anodized reflector
- Remote driver with plug and play connection
- · Powered by Tridonic

| GENERAL INFORMATION | | |
|---------------------|------------|--|
| Wattage | 21W | |
| Lumens Delivered | 1400lm | |
| Lm/W | 66lm/W | |
| Beam Angle | 65 | |
| CRI | 90 | |
| CCT | 4000K | |
| Input | 220-240V | |
| Operating Temp | 0°C - 25°C | |
| SDCM | 3 | |
| UGR | 17 | |
| Cut-Out Size | 125mm | |

| TECHNICAL INFORMATION | | |
|--------------------------------|-------------|--|
| Light Source | LED | |
| Colour / Finish | White | |
| IP Rating | IP44 | |
| Class Protection | 2 | |
| Internal / External | Internal | |
| Surface / Recessed / Suspended | Recessed | |
| Lumen Depreciation | L80 60,000h | |
| Warranty (Years) | 5 | |
| CE Mark | Yes | |
| Diameter | 138 mm | |
| Height | 105 mm | |

- · Anti-glare design to create visual comfort
- · Dimmable and emergency options