

@ansell_lighting f ansellighting Image: Ansell Lighting Image: Compared ansell_lighting

Unity 125 DHP

Unity 125 DHP Downlight Cool White DALI Code: AULED125DHP/DD3

Category	Downlights
Application	Ancillary, Commercial, Education, Hospitality,
	Residential, Retail
Specification	Architectural



PRODUCT FEATURES

- IP44 compact high performance architectural downlight suitable for commercial, hospitality
 and retail applications
- Mirror finished anodized reflector
- Remote driver with plug and play connection
- Powered by Tridonic

(ENERAL INFORMATION
Wattage	28W
Lumens Delivered	2400lm
Lm/W	85lm/W
Beam Angle	65
CRI	90
CCT	4000K
Input	220-240V
Operating Temp	-20°C - 25°C
SDCM	3
UGR	18
Cut-Out Size	125mm
Product Weight without Packaging	0.72 kg

TECHNICAL INFORMATION			
Light Source	LED		
Colour / Finish	White		
IP Rating	IP44		
Class Protection	2		
Internal / External	Internal		
Surface / Recessed / Suspended	Recessed		
Lumen Depreciation	L80 60,000h		
Warranty (Years)	5		
CE Mark	Yes		
Diameter	138 mm		
Height	105 mm		

Die-cast aluminium construction, powder coated and 30° cut-off angle

· Anti-glare design to create visual comfort

· Dimmable and emergency options