



@ansell_lighting



ansellighting



Ansell Lighting






ansell_lighting

Unity 125 DHP

Unity 125 DHP Downlight Cool White Emergency
Code: AULED125DHP/M3

| | |
|---------------|--|
| Category | Downlights |
| Application | Ancillary, Commercial, Education, Hospitality, Residential, Retail |
| Specification | Architectural |



PRODUCT FEATURES

- IP44 compact high performance architectural downlight suitable for commercial, hospitality and retail applications
- Mirror finished anodized reflector
- Remote driver with plug and play connection
- Powered by Tridonic
- Die-cast aluminium construction, powder coated and 30° cut-off angle
- Anti-glare design to create visual comfort
- Dimmable and emergency options

| GENERAL INFORMATION | |
|----------------------------------|------------|
| Wattage | 28W |
| Lumens Delivered | 2400lm |
| Lm/W | 85lm/W |
| Beam Angle | 65 |
| CRI | 90 |
| CCT | 4000K |
| Input | 220-240V |
| Operating Temp | 0°C - 25°C |
| SDCM | 3 |
| UGR | 18 |
| Cut-Out Size | 125mm |
| Product Weight without Packaging | 1.112 kg |

| TECHNICAL INFORMATION | |
|--------------------------------|-------------|
| Light Source | LED |
| Colour / Finish | White |
| IP Rating | IP44 |
| Class Protection | 2 |
| Internal / External | Internal |
| Surface / Recessed / Suspended | Recessed |
| Lumen Depreciation | L80 60,000h |
| Warranty (Years) | 5 |
| CE Mark | Yes |
| Diameter | 138 mm |
| Height | 105 mm |

