











Unity 125 DHP

Unity 125 DHP Downlight Warm White Switch Dim Code: AULED125DHP/WW/DD1/M3

Downlights	
Ancillary, Commercial, Education, Hospitality,	
Residential, Retail	
Architectural	



PRODUCT FEATURES

- IP44 compact high performance architectural downlight suitable for commercial, hospitality and retail applications
- Mirror finished anodized reflector
- Remote driver with plug and play connection
- · Powered by Tridonic

- Die-cast aluminium construction, powder coated and 30° cut-off angle
- · Anti-glare design to create visual comfort
- Dimmable and emergency options

GENERAL INFORMATION		
Wattage	28W	
Lumens Delivered	2300lm	
Lm/W	82lm/W	
Beam Angle	65	
CRI	90	
CCT	3000K	
Input	220-240V	
Operating Temp	0°C - 25°C	
SDCM	3	
UGR	18	
Cut-Out Size	125mm	
Product Weight without Packaging	1.39 kg	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	White	
IP Rating	IP44	
Class Protection	2	
Internal / External	Internal	
Surface / Recessed / Suspended	Recessed	
Lumen Depreciation	L80 60,000h	
Warranty (Years)	5	
CE Mark	Yes	
Diameter	138 mm	
Height	105 mm	