



@ansell\_lighting



ansellighting



Ansell Lighting





ansell\_lighting

# Unity 125 DHP

Unity 125 DHP Downlight Warm White DALI  
Code: AULED125DHP/WW/DD3/M3

|               |  |
|---------------|--|
| Category      | Downlights   |
| Application   | Ancillary, Commercial, Education, Hospitality, Residential, Retail |
| Specification | Architectural  |



## PRODUCT FEATURES

- IP44 compact high performance architectural downlight suitable for commercial, hospitality and retail applications
- Mirror finished anodized reflector
- Remote driver with plug and play connection
- Powered by Tridonic
- Die-cast aluminium construction, powder coated and 30° cut-off angle
- Anti-glare design to create visual comfort
- Dimmable and emergency options

## GENERAL INFORMATION

|                  |            |
|------------------|------------|
| Wattage          | 28W        |
| Lumens Delivered | 2300lm     |
| Lm/W             | 82lm/W     |
| Beam Angle       | 65         |
| CRI              | 90         |
| CCT              | 3000K      |
| Input            | 220-240V   |
| Operating Temp   | 0°C - 25°C |
| SDCM             | 3          |
| UGR              | 18         |
| Cut-Out Size     | 125mm      |

## TECHNICAL INFORMATION

|                                |             |
|--------------------------------|-------------|
| Light Source                   | LED         |
| Colour / Finish                | White       |
| IP Rating                      | IP44        |
| Class Protection               | 2           |
| Internal / External            | Internal    |
| Surface / Recessed / Suspended | Recessed    |
| Lumen Depreciation             | L80 60,000h |
| Warranty (Years)               | 5           |
| CE Mark                        | Yes         |
| Diameter                       | 138 mm      |
| Height                         | 105 mm      |

