



Unity 125 DHP

Unity 125 DHP Downlight Warm White 1-10V Code: AULED125DHP/WW/DD4

Category	Downlights
Application	Ancillary, Commercial, Education, Hospitality,
	Residential, Retail
Specification	Architectural



PRODUCT FEATURES

- IP44 compact high performance architectural downlight suitable for commercial, hospitality and retail applications
- Mirror finished anodized reflector
- Remote driver with plug and play connection
- · Powered by Tridonic

	GENERAL INFORMATION	
Wattage	28W	
Lumens Delivered	2300lm	
Lm/W	82lm/W	
Beam Angle	65	
CRI	90	
CCT	3000K	
Input	220-240V	
Operating Temp	-20°C - 25°C	
SDCM	3	
UGR	18	
Cut-Out Size	125mm	

TECHNICAL INFORMATION			
Light Source	LED		
Colour / Finish	White		
IP Rating	IP44		
Class Protection	2		
Internal / External	Internal		
Surface / Recessed / Suspended	Recessed		
Lumen Depreciation	L80 60,000h		
Warranty (Years)	5		
CE Mark	Yes		
Diameter	138 mm		
Height	105 mm		

Die-cast aluminium construction, powder coated and 30° cut-off angle

· Anti-glare design to create visual comfort

· Dimmable and emergency options

www.ansell-lighting.com Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750

