



Category	Downlights
Application	Ancillary, Commercial, Education, Hospitality, Residential, Retail
Specification	Architectural

Unity 125 DHP

Unity 125 DHP Downlight Warm White

Code: AULED125DHP/WW



PRODUCT FEATURES

- IP44 compact high performance architectural downlight suitable for commercial, hospitality and retail applications
- Mirror finished anodized reflector
- Remote driver with plug and play connection
- Powered by Tridonic
- Die-cast aluminium construction, powder coated and 30° cut-off angle
- Anti-glare design to create visual comfort
- Dimmable and emergency options

GENERAL INFORMATION

Wattage	28W
Lumens Delivered	2300lm
Lm/W	82lm/W
Beam Angle	65
CRI	90
CCT	3000K
Input	220-240V
Operating Temp	-20°C - 25°C
SDCM	3
UGR	18
Cut-Out Size	125mm
Product Weight without Packaging	0.608 kg

TECHNICAL INFORMATION

Light Source	LED
Colour / Finish	White
IP Rating	IP44
Class Protection	2
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Lumen Depreciation	L80 60,000h
Warranty (Years)	5
CE Mark	Yes
Diameter	138 mm
Height	105 mm





Category	Downlights
Application	Ancillary, Commercial, Education, Hospitality, Residential, Retail
Specification	Architectural

Unity 125 DHP

Unity 125 DHP Downlight Warm White
Code: AULED125DHP/WW

