Unity Downlight

Part of the Downlights product category

Model	Unity 125 DHP Downlight Cool White
Code	AULED125DHP
Application	Ancillary, Commercial, Education, Hospitality, Residential, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	28W
Operating Temp	-20°C - 25°C
Lumens Delivered	2400lm
lm/W	85lm/W
CCT	4000K
UGR	18
Beam Angle	65

MATERIAL INFORMATION

Main Material	Aluminium
Diffuser Material	N/A
Product Weight without Packaging	0.52 kg
Colour / Finish	White
Diameter	138 mm
Height	105 mm

TECHNICAL INFORMATION

Class Protection	2
Light Source	LED
SDCM (Initial Macadam)	3
CRI	90
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Power Factor	0.9
L70 @ 25°C	L70 B50 60,000h

PRODUCT FEATURES

- IP44 compact high performance architectural downlight suitable for commercial, hospitality and retail applications
- Die-cast aluminium construction, powder coated and 30° cut-off angle
- Mirror finished anodized reflector
- Anti-glare design to create visual comfort
- Remote driver with plug and play connection





Unity Downlight

Part of the Downlights product category

Model	Unity 125 DHP Downlight Cool White
Code	AULED125DHP
Application	Ancillary, Commercial, Education, Hospitality, Residential, Retail







