



Unity Downlight

Part of the Downlights product category



Model Unity 125 DHP Downlight Cool White
Code AULED125DHP
Application Ancillary, Commercial, Education, Hospitality, Residential, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	28W
Operating Temp	-20°C - 25°C
Lumens Delivered	2400lm
lm/W	85lm/W
CCT	4000K
UGR	18
Beam Angle	65

MATERIAL INFORMATION

Main Material	Aluminium
Diffuser Material	N/A
Product Weight without Packaging	0.52 kg
Colour / Finish	White
Diameter	138 mm
Height	105 mm

TECHNICAL INFORMATION

Class Protection	2
Light Source	LED
SDCM (Initial Macadam)	3
CRI	90
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Power Factor	0.9
L70 @ 25°C	L70 B50 60,000h

PRODUCT FEATURES

- IP44 compact high performance architectural downlight suitable for commercial, hospitality and retail applications
- Die-cast aluminium construction, powder coated and 30° cut-off angle
- Mirror finished anodized reflector
- Anti-glare design to create visual comfort
- Remote driver with plug and play connection





Unity Downlight

Part of the Downlights product category



- Model** Unity 125 DHP Downlight Cool White
- Code** AULED125DHP
- Application** Ancillary, Commercial, Education, Hospitality, Residential, Retail

