



@ansell_lighting



ansellighting



Ansell Lighting







ansell_lighting

Unity 150

Unity 150 Downlight Cool White Switch Dim DALI-
Code: AULED150D/DD1/DM3

| | |
|---------------|--|
| Category | Downlights |
| Application | Ancillary, Commercial, Education, Hospitality, Residential, Retail |
| Specification | Architectural |



PRODUCT FEATURES

- IP44 compact high performance architectural downlight suitable for commercial, hospitality and retail applications
- Mirror finished anodized reflector
- Remote driver with plug and play connection
- Powered by Tridonic
- Die-cast aluminium construction, powder coated and 30° cut-off angle
- Anti-glare design to create visual comfort
- Dimmable and emergency options

GENERAL INFORMATION

| | |
|------------------|------------|
| Wattage | 37W |
| Lumens Delivered | 3200lm |
| Lm/W | 88lm/W |
| Beam Angle | 70 |
| CRI | 90 |
| CCT | 3000K |
| Input | 220-240V |
| Operating Temp | 0°C - 25°C |
| SDCM | 3 |
| UGR | 22 |
| Cut-Out Size | 150mm |

TECHNICAL INFORMATION

| | |
|--------------------------------|-------------|
| Light Source | LED |
| Colour / Finish | White |
| IP Rating | IP44 |
| Class Protection | 2 |
| Internal / External | Internal |
| Surface / Recessed / Suspended | Recessed |
| Lumen Depreciation | L70 50,000h |
| Warranty (Years) | 5 |
| CE Mark | Yes |
| Diameter | 165 mm |
| Height | 137 mm |

