











Unity 150

Unity 150 Downlight Warm White DALI DALI-Code: AULED150D/WW/DD3/DM3

Downlights
Ancillary, Commercial, Education, Hospitality,
Residential, Retail
Architectural



PRODUCT FEATURES

- IP44 compact high performance architectural downlight suitable for commercial, hospitality and retail applications
- Mirror finished anodized reflector

www.ansell-lighting.com

- Remote driver with plug and play connection
- · Powered by Tridonic

- Die-cast aluminium construction, powder coated and 30° cut-off angle
- · Anti-glare design to create visual comfort
- Dimmable and emergency options

GENERAL INFORMATION		
Wattage	37W	
Lumens Delivered	2900lm	
Lm/W	78lm/W	
Beam Angle	70	
CRI	90	
ССТ	3000K	
Input	220-240V	
Operating Temp	0°C - 25°C	
SDCM	3	
UGR	22	
Cut-Out Size	150mm	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	White	
IP Rating	IP44	
Class Protection	2	
Internal / External	Internal	
Surface / Recessed / Suspended	Recessed	
Lumen Depreciation	L70 50,000h	
Warranty (Years)	5	
CE Mark	Yes	
Diameter	165 mm	
Height	137 mm	

Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750