













Unity 150

Unity 150 Downlight Warm White DALI Emergency Code: AULED150D/WW/DD3/M3

Specification	Architectural	
	Residential, Retail	
Application	Ancillary, Commercial, Education, Hospitality,	
Category	Downlights	









PRODUCT FEATURES

- IP44 compact high performance architectural downlight suitable for commercial, hospitality and retail applications
- Mirror finished anodized reflector
- Remote driver with plug and play connection
- · Powered by Tridonic

- Die-cast aluminium construction, powder coated and 30° cut-off angle
- · Anti-glare design to create visual comfort
- Dimmable and emergency options

GENERAL INFORMATION			
Wattage	37W		
Lumens Delivered	2900lm		
Lm/W	78lm/W		
Beam Angle	70		
CRI	90		
CCT	3000K		
Input	220-240V		
Operating Temp	0°C - 25°C		
SDCM	3		
UGR	22		
Cut-Out Size	150mm		
Product Weight without Packagi	g 0.01 kg		

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	White	
IP Rating	IP44	
Class Protection	2	
Internal / External	Internal	
Surface / Recessed / Suspended	Recessed	
Lumen Depreciation	L70 50,000h	
Warranty (Years)	5	
CE Mark	Yes	
Diameter	165 mm	
Height	137 mm	

Belfast: +44 (0) 2890 773750