











## Unity 150

Unity 150 Downlight Warm White DALI Self-Test Code: AULED150D/WW/DD3/SM3

| Category      | Downlights                                     |
|---------------|--|
| Application   | Ancillary, Commercial, Education, Hospitality, |
|               | Residential, Retail                            |
| Specification | Architectural                                  |
|               |  |



## PRODUCT FEATURES

- IP44 compact high performance architectural downlight suitable for commercial, hospitality and retail applications
- Mirror finished anodized reflector

www.ansell-lighting.com

- Remote driver with plug and play connection
- · Powered by Tridonic

- Die-cast aluminium construction, powder coated and 30° cut-off angle
- · Anti-glare design to create visual comfort
- Dimmable and emergency options

| GENERAL INFORMATION |            |  |
|---------------------|------------|--|
| Wattage             | 37W        |  |
| Lumens Delivered    | 2900lm     |  |
| Lm/W                | 78lm/W     |  |
| Beam Angle          | 70         |  |
| CRI                 | 90         |  |
| ССТ                 | 3000K      |  |
| Input               | 220-240V   |  |
| Operating Temp      | 0°C - 25°C |  |
| SDCM                | 3          |  |
| UGR                 | 22         |  |
| Cut-Out Size        | 150mm      |  |

| TECHNICAL INFORMATION          |             |  |  |
|--------------------------------|-------------|--|--|
| Light Source                   | LED         |  |  |
| Colour / Finish                | White       |  |  |
| IP Rating                      | IP44        |  |  |
| Class Protection               | 2           |  |  |
| Internal / External            | Internal    |  |  |
| Surface / Recessed / Suspended | Recessed    |  |  |
| Lumen Depreciation             | L70 50,000h |  |  |
| Warranty (Years)               | 5           |  |  |
| CE Mark                        | Yes         |  |  |
| Diameter                       | 165 mm      |  |  |
| Height                         | 137 mm      |  |  |

Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750