







Unity 150

33W Unity 150 3000K LED Downlight
Code: AULED150D/WW

| | |
|---------------|--|
| Category | Downlights |
| Application | Ancillary, Commercial, Education, Hospitality, Residential, Retail |
| Specification | Architectural |



PRODUCT FEATURES

- IP44 compact high performance architectural downlight suitable for commercial, hospitality and retail applications
- Mirror finished anodized reflector
- Remote driver with plug and play connection
- Powered by Tridonic
- Die-cast aluminium construction, powder coated and 30° cut-off angle
- Anti-glare design to create visual comfort
- Dimmable and emergency options

| GENERAL INFORMATION | |
|----------------------------------|--------------|
| Wattage | 36 |
| Lumens Delivered | 2900lm |
| Lm/W | 78lm/W |
| Beam Angle | 70 |
| CRI | 90 |
| CCT | 3000K |
| Input | 220/240V |
| Operating Temp | -20°C - 25°C |
| SDCM | 3 |
| UGR | 22 |
| Cut-Out Size | 150 |
| Energy efficiency class | E |
| Product Weight without Packaging | 1.041 kg |

| TECHNICAL INFORMATION | |
|--------------------------------|----------|
| Light Source | LED |
| Colour / Finish | White |
| IP Rating | IP44 |
| Class Protection | 2 |
| Internal / External | Internal |
| Surface / Recessed / Suspended | Recessed |
| Warranty (Years) | 5 |
| CE Mark | Yes |
| Diameter | 165 mm |
| Height | 132 mm |

