



Unity Downlight

Part of the Downlights product category



Model 33W Unity 150 4000K LED Downlight
Code AULED150D
Application Ancillary, Commercial, Education, Hospitality, Residential, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	36
Operating Temp	-20°C - 25°C
Lumens Delivered	3200lm
lm/W	88lm/W
CCT	4000K
UGR	22
Beam Angle	70

MATERIAL INFORMATION

Main Material	Aluminium
Product Weight without	1.06 kg
Packaging	
Colour / Finish	White
Diameter	165 mm
Height	137 mm

TECHNICAL INFORMATION

Class Protection	2
Light Source	LED
SDCM (Initial Macadam)	3
CRI	90
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Power Factor	0.98
L70 @ 25°C	L70 B50 60,000h

PRODUCT FEATURES

- IP44 compact high performance architectural downlight suitable for commercial, hospitality and retail applications
- Die-cast aluminium construction, powder coated and 30° cut-off angle
- Mirror finished anodized reflector
- Anti-glare design to create visual comfort
- Remote driver with plug and play connection





Unity Downlight



Part of the Downlights product category

- Model** 33W Unity 150 4000K LED Downlight
- Code** AULED150D
- Application** Ancillary, Commercial, Education, Hospitality, Residential, Retail

