Unity Downlight

Part of the Downlights product category

5YR | IP44 | ON-SITE WARRANTY 2 YEARS

Model	33W Unity 150 4000K LED Downlight
Code	AULED150D
Application	Ancillary, Commercial, Education, Hospitality, Residential, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	36
Operating Temp	-20°C - 25°C
Lumens Delivered	3200lm
lm/W	88lm/W
CCT	4000K
UGR	22
Beam Angle	70

MATERIAL INFORMATION

Main Material	Aluminium
Product Weight without Packaging	1.06 kg
Colour / Finish	White
Diameter	165 mm
Height	137 mm

TECHNICAL INFORMATION

Class Protection	2
Light Source	LED
SDCM (Initial Macadam)	3
CRI	90
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Power Factor	0.98
L70 @ 25°C	L70 B50 60,000h

PRODUCT FEATURES

- IP44 compact high performance architectural downlight suitable for commercial, hospitality and retail applications
- Die-cast aluminium construction, powder coated and 30° cut-off angle
- Mirror finished anodized reflector
- Anti-glare design to create visual comfort
- Remote driver with plug and play connection





Unity Downlight

Part of the Downlights product category

Model	33W Unity 150 4000K LED Downlight
Code	AULED150D
Application	Ancillary, Commercial, Education, Hospitality, Residential, Retail







