



Downlights	
Ancillary, Commercial, Education, Hospitality,	
Residential, Retail	
Architectural	

Unity 150

33W Unity 150 4000K LED Downlight

Code: AULED150D







PRODUCT FEATURES

- IP44 compact high performance architectural downlight suitable for commercial, hospitality and retail applications
- Mirror finished anodized reflector
- Remote driver with plug and play connection
- · Powered by Tridonic

- Die-cast aluminium construction, powder coated and 30° cut-off angle
- · Anti-glare design to create visual comfort
- Dimmable and emergency options

GI	ENERAL INFORMATION
Wattage	36
Lumens Delivered	3200lm
Lm/W	88lm/W
Beam Angle	70
CRI	90
ССТ	4000K
Input	220-240V
Operating Temp	-20°C - 25°C
SDCM	3
UGR	22
Cut-Out Size	150
Energy efficiency class	E
Product Weight without Packaging	1.06 kg

Belfast: +44 (0) 2890 773750

Warrington: +44 (0) 1942 433333

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	White	
IP Rating	IP44	
IK Rating	IKO2	
Class Protection	2	
Internal / External	Internal	
Surface / Recessed / Suspended	Recessed	
Warranty (Years)	5	
CE Mark	Yes	
Diameter	165 mm	
Height	137 mm	











Category	Downlights	
Application	Ancillary, Commercial, Education, Hospitality,	
	Residential, Retail	
Specification	Architectural	

Unity 150

33W Unity 150 4000K LED Downlight **Code**: AULED150D









