




Unity 150 DHP

Unity 150 DHP Downlight Cool White DSI Code: AULED150DHP/DD2/M3





Category


Application

Specification

Downlights

Architectural

Residential, Retail



Ancillary, Commercial, Education, Hospitality,

PRODUCT FEATURES

- IP44 compact high performance architectural downlight suitable for commercial, hospitality
 and retail applications
- Mirror finished anodized reflector
- Remote driver with plug and play connection
- Powered by Tridonic

| GENERAL INFORMATION | | |
|-------------------------------|-------------|--|
| Wattage | 41W | |
| Lumens Delivered | 3900lm | |
| Lm/W | 95lm/W | |
| Beam Angle | 70 | |
| CRI | 90 | |
| ССТ | 4000K | |
| Input | 220-240V | |
| Operating Temp | 0°C - 25°C | |
| SDCM | 3 | |
| UGR | 22 | |
| Cut-Out Size | 150mm | |
| Product Weight without Packag | ing 0.01 kg | |

| TECHNICAL INFORMATION | | |
|--------------------------------|-------------|--|
| Light Source | LED | |
| Colour / Finish | White | |
| IP Rating | IP44 | |
| Class Protection | 2 | |
| Internal / External | Internal | |
| Surface / Recessed / Suspended | Recessed | |
| Lumen Depreciation | L70 50,000h | |
| Warranty (Years) | 5 | |
| CE Mark | Yes | |
| Diameter | 165 mm | |
| Height | 137 mm | |

- Die-cast aluminium construction, powder coated and 30° cut-off angle
- Anti-glare design to create visual comfort
- Dimmable and emergency options

