



Unity 150 DHP

Unity 150 DHP Downlight Cool White DALI DALI-Code: AULED150DHP/DD3/DM3

Category	Downlights
Application	Ancillary, Commercial, Education, Hospitality,
	Residential, Retail
Specification	Architectural



PRODUCT FEATURES

- IP44 compact high performance architectural downlight suitable for commercial, hospitality
 and retail applications
- Mirror finished anodized reflector
- Remote driver with plug and play connection
- Powered by Tridonic

GENERAL INFORMATION		
Wattage	41W	
Lumens Delivered	3900lm	
Lm/W	95lm/W	
Beam Angle	70	
CRI	90	
CCT	4000K	
Input	220-240V	
Operating Temp	0°C - 25°C	
SDCM	3	
UGR	22	
Cut-Out Size	150mm	

TECHNICAL INFORMATION			
Light Source	LED		
Colour / Finish	White		
IP Rating	IP44		
Class Protection	2		
Internal / External	Internal		
Surface / Recessed / Suspended	Recessed		
Lumen Depreciation	L70 50,000h		
Warranty (Years)	5		
CE Mark	Yes		
Diameter	165 mm		
Height	137 mm		

- Die-cast aluminium construction, powder coated and 30° cut-off angle

- Anti-glare design to create visual comfort
- Dimmable and emergency options