




Unity 150 DHP

Unity 150 DHP Downlight Cool White DALI Code: AULED150DHP/DD3/M3





Category

Application

Specification

Downlights

Architectural

Residential, Retail



Ancillary, Commercial, Education, Hospitality,

PRODUCT FEATURES

- IP44 compact high performance architectural downlight suitable for commercial, hospitality
 and retail applications
- Mirror finished anodized reflector
- Remote driver with plug and play connection
- Powered by Tridonic

GENERAL INFORMATION		
Wattage	41W	
Lumens Delivered	3900lm	
Lm/W	95lm/W	
Beam Angle	70	
CRI	90	
ССТ	4000K	
Input	220-240V	
Operating Temp	0°C - 25°C	
SDCM	3	
UGR	22	
Cut-Out Size	150mm	
Product Weight without Packag	ing 0.01 kg	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	White	
IP Rating	IP44	
Class Protection	2	
Internal / External	Internal	
Surface / Recessed / Suspended	Recessed	
Lumen Depreciation	L70 50,000h	
Warranty (Years)	5	
CE Mark	Yes	
Diameter	165 mm	
Height	137 mm	

- Die-cast aluminium construction, powder coated and $30^\circ\,\text{cut-off}$ angle
- Anti-glare design to create visual comfort
- Dimmable and emergency options