











Unity 150 DHP

Unity 150 DHP Downlight Cool White 1-10V DALI-Code: AULED150DHP/DD4/DM3

| Category | Downlights |
|---------------|--|
| Application | Ancillary, Commercial, Education, Hospitality, |
| | Residential, Retail |
| Specification | Architectural |
| | |



PRODUCT FEATURES

- IP44 compact high performance architectural downlight suitable for commercial, hospitality Die-cast aluminium construction, powder coated and 30° cut-off angle and retail applications
- Mirror finished anodized reflector

www.ansell-lighting.com

- Remote driver with plug and play connection
- · Powered by Tridonic

- · Anti-glare design to create visual comfort
- Dimmable and emergency options

| GENERAL INFORMATION | | |
|---------------------|------------|--|
| Wattage | 41W | |
| Lumens Delivered | 3900lm | |
| Lm/W | 95lm/W | |
| Beam Angle | 70 | |
| CRI | 90 | |
| CCT | 4000K | |
| Input | 220-240V | |
| Operating Temp | 0°C - 25°C | |
| SDCM | 3 | |
| UGR | 22 | |
| Cut-Out Size | 150mm | |

| TECHNICAL INFORMATION | | | |
|--------------------------------|-------------|--|--|
| Light Source | LED | | |
| Colour / Finish | White | | |
| IP Rating | IP44 | | |
| Class Protection | 2 | | |
| Internal / External | Internal | | |
| Surface / Recessed / Suspended | Recessed | | |
| Lumen Depreciation | L70 50,000h | | |
| Warranty (Years) | 5 | | |
| CE Mark | Yes | | |
| Diameter | 165 mm | | |
| Height | 137 mm | | |

Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750