





Unity 150 DHP

Unity 150 DHP Downlight Cool White 1-10V Code: AULED150DHP/DD4





Category

Application

Specification

Downlights

Architectural

Residential, Retail



Ancillary, Commercial, Education, Hospitality,

PRODUCT FEATURES

- IP44 compact high performance architectural downlight suitable for commercial, hospitality
 and retail applications
- Mirror finished anodized reflector
- Remote driver with plug and play connection
- Powered by Tridonic

GENERAL INFORMATION	
Wattage	41W
Lumens Delivered	3900lm
Lm/W	95lm/W
Beam Angle	70
CRI	90
ССТ	4000K
Input	220-240V
Operating Temp	-20°C - 25°C
SDCM	3
UGR	22
Cut-Out Size	150mm
Product Weight without Packaging	0.01 kg

TECHNICAL INFORMATION	
Light Source	LED
Colour / Finish	White
IP Rating	IP44
Class Protection	2
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Lumen Depreciation	L70 50,000h
Warranty (Years)	5
CE Mark	Yes
Diameter	165 mm
Height	137 mm

- Die-cast aluminium construction, powder coated and 30° cut-off angle
- Anti-glare design to create visual comfort
- Dimmable and emergency options

www.ansell-lighting.com Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750