





Unity 150 DHP

Unity 150 DHP Downlight Cool White DALI-Code: AULED150DHP/DM3





Category

Application

Specification

Downlights

Architectural

Residential, Retail



Ancillary, Commercial, Education, Hospitality,

PRODUCT FEATURES

- IP44 compact high performance architectural downlight suitable for commercial, hospitality
 and retail applications
- Mirror finished anodized reflector
- Remote driver with plug and play connection
- Powered by Tridonic

GENERAL INFORMATION				
Wattage	41W			
Lumens Delivered	3900lm			
Lm/W	95lm/W			
Beam Angle	70			
CRI	90			
CCT	4000K			
Input	220-240V			
Operating Temp	0°C - 25°C			
SDCM	3			
UGR	22			
Cut-Out Size	150mm			

TECHNICAL INFORMATION				
Light Source	LED			
Colour / Finish	White			
IP Rating	IP44			
Class Protection	2			
Internal / External	Internal			
Surface / Recessed / Suspended	Recessed			
Lumen Depreciation	L70 50,000h			
Warranty (Years)	5			
CE Mark	Yes			
Diameter	165 mm			
Height	137 mm			

- Die-cast aluminium construction, powder coated and $30^\circ\,\text{cut-off}$ angle

- Anti-glare design to create visual comfort
- Dimmable and emergency options

www.ansell-lighting.com	Warrington: +	+44 (0) 1942 433333	Belfast: +44 (0) 2890 773750
-------------------------	---------------	---------------------	------------------------------

