


Ancillary, Commercial, Education, Hospitality,

Unity 150

Unity 150 Wallwash Cool White DALI Code: AULED150WW/DD3





Category

Application

Specification

Downlights

Architectural

Residential, Retail



PRODUCT FEATURES

- Recessed adjustable architectural wallwash with 355° rotation suitable for commercial, hospitality and retail applications
- 30° cut-off angle in the horizontal position
- Remote driver with plug and play connection
- Powered by Tridonic

GENERAL INFORMATION		
Wattage	28W	
Lumens Delivered	2700lm	
Lm/W	93lm/W	
Beam Angle	55	
CRI	90	
ССТ	4000K	
Input	220-240V	
Operating Temp	-20°C - 25°C	
SDCM	3	
UGR	16	
Cut-Out Size	150mm	
Product Weight without Packagir	ng 0.766 kg	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	White	
IP Rating	IP20	
Class Protection	2	
Internal / External	Internal	
Surface / Recessed / Suspended	Recessed	
Lumen Depreciation	L70 50,000h	
Warranty (Years)	5	
CE Mark	Yes	
Diameter	162 mm	
Height	138 mm	

- Adjustable tilt angle from -15° to 45°
- · Die-cast aluminium body and heatsink for good thermal management
- Dimmable options

