







Unity 150

Unity 150 Wallwash Cool White OCTO Smart
Code: AULED150WW/OCTO

| | |
|---------------|--|
| Category | Downlights |
| Application | Ancillary, Commercial, Education, Hospitality, Residential, Retail |
| Specification | Architectural |



PRODUCT FEATURES

- Recessed adjustable architectural wallwash with 355° rotation suitable for commercial, hospitality and retail applications
- 30° cut-off angle in the horizontal position
- Remote driver with plug and play connection
- Powered by Tridonic
- Adjustable tilt angle from -15° to 45°
- Die-cast aluminium body and heatsink for good thermal management
- Dimmable options

| GENERAL INFORMATION | |
|----------------------------------|--------------|
| Wattage | 28W |
| Lumens Delivered | 2700lm |
| Lm/W | 93lm/W |
| Beam Angle | 55 |
| CRI | 90 |
| CCT | 4000K |
| Input | 220/240V |
| Operating Temp | -20°C - 25°C |
| SDCM | 3 |
| UGR | 16 |
| Cut-Out Size | 150mm |
| Product Weight without Packaging | 1.2 kg |

| TECHNICAL INFORMATION | |
|--------------------------------|-------------|
| Light Source | LED |
| Colour / Finish | White |
| IP Rating | IP20 |
| Class Protection | 2 |
| Internal / External | Internal |
| Surface / Recessed / Suspended | Recessed |
| Lumen Depreciation | L70 50,000h |
| Warranty (Years) | 5 |
| CE Mark | Yes |
| Diameter | 162 mm |
| Height | 138 mm |

