



Unity 150

Unity 150 Wallwash Warm White 1-10V Code: AULED150WW/WW/DD4

Category	Downlights	
Application	Ancillary, Commercial, Education, Hospitality,	
	Residential, Retail	
Specification	Architectural	



- Recessed adjustable architectural wallwash with 355° rotation suitable for commercial,
- hospitality and retail applications
- + $\,30^\circ\,\text{cut-off}$ angle in the horizontal position
- Remote driver with plug and play connection
- Powered by Tridonic

GENERAL INFORMATION			
Wattage	28W		
Lumens Delivered	2500lm		
Lm/W	86lm/W		
Beam Angle	55		
CRI	90		
CCT	3000K		
Input	220/240V		
Operating Temp	-20°C - 25°C		
SDCM	5		
UGR	16		
Cut-Out Size	150mm		
Product Weight without Packaging	0.01 kg		

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	White	
IP Rating	IP20	
Class Protection	2	
Internal / External	Internal	
Surface / Recessed / Suspended	Recessed	
Lumen Depreciation	L70 50,000h	
Warranty (Years)	5	
CE Mark	Yes	
Diameter	162 mm	
Height	138 mm	

- Adjustable tilt angle from -1.5° to 45°
- Die-cast aluminium body and heatsink for good thermal management
- Dimmable options